



# KOOTENAY FILTER™

Kootenay Filter

 [kootenayfilter.com/product/kfi-1000sl-without-flange/](http://kootenayfilter.com/product/kfi-1000sl-without-flange/)

**KFI 1000SL**

RECOMMENDED FLANGES 8" Wide / 10" / 12" / 14"			PRE-FILTER INSTALLED Replacement Pre-Filter PF1000SL
<b>AIR FLOW</b>	<b>CFM</b>	<b>M<sup>3</sup></b>	<b>Diameter</b> 40 cm / 15.8" <b>Length</b> 100 cm / 39.4" <b>Carbon Weight</b> 33 Kg / 72.8 lbs. Total Weight 47 Kg / 103.4 lbs. <b>Carbon Bed Depth</b> 6.5 cm / 2.55" <b>Carbon Type</b> Pelletized
<b>Max. Exhaust</b>	840	1400	
<b>Scrubbing Max. Recirculating</b>	1680	2800	

STANDARD LINE INDUSTRIAL CARBON FILTERS 4" to 16" / 206 - 1260 CFM  
 STANDARD LINE FILTERS USE PELLETIZED ACTIVATED CARBON - VERY LOW PRESSURE DROP  
 PROVEN DESIGN WITH 100% ACTIVATED CARBON - LONG SERVICE LIFE  
 MACHINE PACKED FOR CONSISTENT QUALITY - SCREENED CARBON

PLEASE RECYCLE

**AIR FILTRATION & VENTILATION**  
[kootenayfilter.com](http://kootenayfilter.com)

Made in Canada



KFI 1000SL Without Flange

Carbon: Pelletized Activated Carbon CKV-4

Prefilter installed: Yes

Replacement Prefilter SKU: PF1000SL

**CFM/M3 Ratings:**

Max Exhaust CFM – 840

Max Recirculate CFM – 1680

Max Exhaust M3 – 1400

Max Recirculating M3 – 2800

SKU: SL1000 Category: [Standard Line Filters](#)

**Description**

---

<b>SKU:</b>	<b>SL1000</b>	
Carbon:	Pelletized Activated Carbon CKV-4	
Flanges Available:	8" Wide / 10" / 12" / 14"	SKU: FL8W / FL10 / FL12 / FL14
Prefilter Installed:	Yes	
Replacement Prefilter SKU:	PF1000SL	
Measurements and Weights:	Imperial	Metric
Outside Diameter:	15.8"	40cm
Lengths:	39.4	100cm
Total Weight:	103.4lbs	47kg
Carbon Weight:	72.8lbs	33kg
Carbon Bed:	2.55"	6.5cm
Max Operating Temperature:	176F	80°C
Minimum Recommended Airflow:	420CFM	
Pressure Drop at Max CFM:	180pa / 0.75"wg	

---

**SKU:** SL1000

---

<b>Possible Fan Combinations:</b>	<b>Exhaust</b>	<b>Recirculating</b>
	<u>Renegade FR 8</u> <u>Renegade EC Pro 8</u> <u>Renegade EC Pro 10</u> <u>Renegade Silent 8</u> <u>Renegade Silent 10</u>	<u>Renegade FR 10</u> <u>Renegade FR 12</u> <u>Renegade FR 14</u> <u>Renegade EC Pro 10</u> <u>Renegade EC Pro 14</u> <u>Renegade Silent 10</u> <u>Renegade Silent 12</u>

---

## Standard Line Filters - Details

---

KFI Standard Line filters are made with virgin activated CKV-4 carbon. Each filter is hand made in North America using a proven filing process making this product one of the best filters on the market. At KFI we take pride in our products and ensure our customers receive the highest quality products available.

- Virgin activated, pelletized CKV-4 Carbon
- Dedusted and screened
- Low pressure drop rated @0.1 sec. contact time
- Long service life
- Max operating temperature 80°C / 176°F
- Max allowed humidity 70% (short term only)
- Prefilter installed
- Robust galvanized steel housing
- Single packaged and sealed for storage
- Made in North America
- 2.55" carbon bed
- KFI flanges sold separately, available in 4" to 16"