



KOOTENAY FILTER™

Kootenay Filter

 kootenayfilter.com/product/kfi-750-without-flange/



KFI 750
STANDARD LINE™
INDUSTRIAL CARBON FILTER

RECOMMENDED FLANGES			PRE-FILTER INSTALLED Replacement Pre-Filter PF750
6" Wide / 8" Wide / 10" / 12"			
AIR FLOW	CFM	M ³	Diameter 40 cm / 15.8" Length 75 cm / 29.5" Carbon Weight 25 Kg / 55.1 lbs. Total Weight 35 Kg / 77 lbs. Carbon Bed Depth 6.5 cm / 2.55" Carbon Type Pelletized <small>© weight for moisture is variable and a result of carbon being a natural product.</small>
Max. Exhaust	600	1000	
Scrubbing Max. Recirculating	1200	2000	

STANDARD LINE INDUSTRIAL CARBON FILTERS 4" to 16" / 206 - 1260 CFM
 STANDARD LINE FILTERS USE PELLETIZED ACTIVATED CARBON - VERY LOW PRESSURE DROP
 PROVEN DESIGN WITH 100% ACTIVATED CARBON - LONG SERVICE LIFE
 MACHINE PACKED FOR CONSISTENT QUALITY - SCREENED CARBON

PLEASE RECYCLE 

AIR FILTRATION & VENTILATION
kootenayfilter.com



KFI 750 Without Flange

Carbon: Pelletized Activated Carbon CKV-4

Prefilter installed: Yes

Replacement Prefilter SKU: PF750

CFM/M3 Ratings:

Max Exhaust CFM – 600

Max Recirculate CFM – 1200

Max Exhaust M3 – 1000

Max Recirculating M3 – 2000

SKU: SL750 Category: Standard Line Filters

Description

SKU:	SL750	
Carbon:	Pelletized Activated Carbon CKV-4	
Flanges Available:	6" Wide / 8" Wide/ 10"/ 12"	SKU: FL6W / FL8W / FL10 / FL12
Prefilter Installed:	Yes	
Replacement Prefilter SKU:	FL6W	
Measurements and Weights:	Imperial	Metric
Outside Diameter:	15.8"	40cm
Lengths:	29.5	75cm
Total Weight:	77.0lbs	35kg
Carbon Weight:	55.1lbs	25kg
Carbon Bed:	2.55"	6.5cm
Max Operating Temperature:	176F	80°C
Minimum Recommended Airflow:	300CFM	
Pressure Drop at Max CFM:	180pa / 0.75"wg	

SKU: SL750

Possible Fan Combinations:	Exhaust	Recirculating
	<u>Renegade FR 8</u> <u>Renegade EC Pro 8</u> <u>Renegade Silent 8</u>	<u>Renegade FR 10</u> <u>Renegade EC Pro 8</u> <u>Renegade EC Pro 10</u> <u>Renegade Silent 10</u> <u>Renegade Silent 12</u>

Standard Line Filters - Details

KFI Standard Line filters are made with virgin activated CKV-4 carbon. Each filter is hand made in North America using a proven filing process making this product one of the best filters on the market. At KFI we take pride in our products and ensure our customers receive the highest quality products available.

- Virgin activated, pelletized CKV-4 Carbon
- Dedusted and screened
- Low pressure drop rated @0.1 sec. contact time
- Long service life
- Max operating temperature 80°C / 176°F
- Max allowed humidity 70% (short term only)
- Prefilter installed
- Robust galvanized steel housing
- Single packaged and sealed for storage
- Made in North America
- 2.55" carbon bed
- KFI flanges sold separately, available in 4" to 16"