



# KOOTENAY FILTER™

Kootenay Filter

 [kootenayfilter.com/product/kfi-1500sl-without-flange/](http://kootenayfilter.com/product/kfi-1500sl-without-flange/)



**KFI 1500SL**

RECOMMENDED FLANGES 8" Wide / 10" / 12" / 14"			PRE-FILTER INSTALLED Replacement Pre-Filter PF1500SL
AIR FLOW	CFM	M <sup>3</sup>	Diameter 40 cm / 15.8"
Max. Exhaust	1260	2100	Length 150 cm / 59.1"
Scrubbing Max. Recirculating	2520	4200	Carbon Weight 50 Kg / 110.2 lbs.
			Total Weight 68 Kg / 150 lbs.
			Carbon Bed Depth 6.5 cm / 2.55"
			Carbon Type Pelletized

STANDARD LINE INDUSTRIAL CARBON FILTERS 4" to 16" / 206 - 1260 CFM  
STANDARD LINE FILTERS USE PELLETIZED ACTIVATED CARBON - VERY LOW PRESSURE DROP  
PROVEN DESIGN WITH 100% ACTIVATED CARBON - LONG SERVICE LIFE  
MACHINE PACKED FOR CONSISTENT QUALITY - SCREENED CARBON

PLEASE RECYCLE

**AIR FILTRATION & VENTILATION**  
[kootenayfilter.com](http://kootenayfilter.com)

Made in Canada  
SKU: SL1500



KFI 1500SL Without Flange

Carbon: Pelletized Activated Carbon CKV-4

Prefilter installed: Yes

Replacement Prefilter SKU: PF1500SL

**CFM/M3 Ratings:**

Max Exhaust CFM – 1260

Max Recirculate CFM – 2520

Max Exhaust M3 – 2100

Max Recirculating M3 – 4200

SKU: SL1500 Category: [Standard Line Filters](#)

**Description**

---

<b>SKU:</b>	<b>SL1500</b>	
Carbon:	Pelletized Activated Carbon CKV-4	
Flanges Available:	8" Wide / 10" / 12" / 14"	SKU: FL8W / FL10 / FL12 / FL14
Prefilter Installed:	Yes	
Replacement Prefilter SKU:	PF1500SL	
Measurements and Weights:	Imperial	Metric
Outside Diameter:	15.8"	40cm
Lengths:	59.1	150cm
Total Weight:	150.0lbs	68kg
Carbon Weight:	110.2lbs	50kg
Carbon Bed:	2.55"	6.5cm
Max Operating Temperature:	176F	80°C
Minimum Recommended Airflow:	630CFM	
Pressure Drop at Max CFM:	180pa / 0.75"wg	

---

**SKU:** SL1500

---

<b>Possible Fan Combinations:</b>	<b>Exhaust</b>	<b>Recirculating</b>
	<u>Renegade FR 10</u> <u>Renegade EC Pro 8</u> <u>Renegade EC Pro 10</u> <u>Renegade EC Pro 14</u> <u>Renegade Silent 10</u>	<u>Renegade FR 12</u> <u>Renegade FR 14</u> <u>Renegade EC Pro 14</u> <u>Renegade Silent 10</u> <u>Renegade Silent 12</u>

---

## Standard Line Filters - Details

---

KFI Standard Line filters are made with virgin activated CKV-4 carbon. Each filter is hand made in North America using a proven filing process making this product one of the best filters on the market. At KFI we take pride in our products and ensure our customers receive the highest quality products available.

- Virgin activated, pelletized CKV-4 Carbon
- Dedusted and screened
- Low pressure drop rated @0.1 sec. contact time
- Long service life
- Max operating temperature 80°C / 176°F
- Max allowed humidity 70% (short term only)
- Prefilter installed
- Robust galvanized steel housing
- Single packaged and sealed for storage
- Made in North America
- 2.55" carbon bed
- KFI flanges sold separately, available in 4" to 16"