

# CLEARLY

## Membrane System Antiscalant



### APPLICATION

Khemical Clearly Membrane should be injected into the feed stream prior to the static mixer and cartridge filter. Effective pH range is 5.0-10. If frozen, it may be thawed and mixed before use. Stability is excellent, but best used within 12 months.

### FORM: LIQUID

Maximum Use Level is 59 Mg/L

### DANGER!

MAY CAUSE EYE BURNS. MAY IRRITATE EYES, SKIN AND RESPIRATORY TRACT. Use with adequate ventilation. Avoid contact with skin and clothing. Wash thoroughly after handling.

HANDLING: Wear goggles or face shield, protective gloves, and protective clothing when handling. Avoid prolonged or repeated breathing of dust (powder) and (vapor) solutions. Harmful if swallowed. Use adequate ventilation. See SDS.

### PRECAUTIONS FOR SAFE HANDLING AND USE

Stop spill/release if possible with minimal risk. Dike far ahead of spill for later recovery or disposal. Notify appropriate agencies. Immediate clean up recommended.

### HAZARD STATEMENTS

H318 Causes serious eye damage.



**55 GALLON**

LOT NUMBER:

NET CONTENTS:

Gallons    Pounds    Liters    Kilograms

### EMERGENCY RESPONSE

FIRST AID: In case of skin contact, flush with plenty of water for at least 15 minutes. If swallowed, rinse mouth. Drink water. Do NOT induce vomiting. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Never give anything by mouth to an unconscious person. In case of inhalation or suspicion of inhalation move patient at once to fresh air and call a physician.

MORR, Inc.

6500 Flotilla Street  
Commerce, CA 90040  
office@MORR.com  
855-TRY-MORR  
www.MORR.com

CHEMTREC 24 Hr. Emergency Phone:  
(800) 424-9300

**NKH351**