

Mixrite Comparison Chart

Model		Options	Max Flow	Min Flow	Pressure	Induction Range		Connection
MixRite	Dosatron					Dosamatic	Ratio	
566AG		1% Fixed Dosage, EPDM Seals	11 GPM	.09 GPM	2.9-120 PSI	1:100 FIXED	1%	3/4" NPT
568AG		1 oz/gal Fixed Dosage, EPDM Seals	11 GPM	.09 GPM	2.9-120 PSI	1:128 FIXED	0.80%	3/4" NPT
569CWONOFF		0.1-0.9%, on/off Aflas Seals, SS Springs	11 GPM	.09 GPM	2.9-120 PSI	1:985 to 1:111	.1-.9%	3/4" NPT
569PVDFONOFF		.1-.9% on/off, PVDF, Viton Seals, HSTY Springs	11 GPM	.09 GPM	2.9-120 PSI	1:985 to 1:111	.1-.9%	3/4" NPT
1401A		.1-.9% HSTY Springs, Aflas Seals	14 GPM	.13 GPM	2.9-120 PSI	1:985 to 1:111	.1-.9%	3/4" NPT
1401M		.1-.9% on/off, HSTY Springs, Aflas Seals	14 GPM	.13 GPM	2.9-120 PSI	1:985 to 1:111	.1-.9%	3/4" NPT
	DM11F		11 GPM	.02 GPM	1.5-85 PSI	1:128 fixed	0.80%	3/4" NPT
	D25F		11 GPM	.05 GPM	4.3-85 PSI	1:128 fixed	0.80%	3/4" NPT
	DI 1500	PVDF, PAA seals, Hastelloy	11 GPM	.05 GPM	4.3-85 PSI	1:1500 to 1:500	.07-.2%	3/4" NPT
	D25RE1500	PVDF, bypass	11 GPM	.05 GPM	4.3-85 PSI	1:1500 to 1:500	.07-.2%	3/4" NPT
		Mini Dos-0.4%	12 GPM	.03 GPM	6-140 PSI	1:4000 to 1:250	.025-.4%	3/4" NPT
570CW		.3-2%, Aflas Seals, SS Springs	11 GPM	.09 GPM	2.9-120 PSI	1:300 to 1:50	.3-2%	3/4" NPT
571CW		.3-2% on/off, Aflas Seals, SS Springs	11 GPM	.09 GPM	2.9-120 PSI	1:300 to 1:50	.3-2%	3/4" NPT
570PVDF		.3-2%, PVDF, Viton Seals, HSTY Springs	11 GPM	.09 GPM	2.9-120 PSI	1:300 to 1:50	.3-2%	3/4" NPT
571PVDF		.3-2% on/off, PVDF, Viton Seals, HSTY Springs	11 GPM	.09 GPM	2.9-120 PSI	1:300 to 1:50	.3-2%	3/4" NPT
1402A		.3-2%, Aflas Seals, HSTY Springs	14 GPM	.09 GPM	2.9-120 PSI	1:300 to 1:50	.3-2%	3/4" NPT
1402M		.3-2%, On/Off Aflas Seals, HSTY Springs	14 GPM	.09 GPM	2.9-120 PSI	1:300 to 1:50	.3-2%	3/4" NPT
	D25RE2	PVDF, Side Inject, Bypass	11 GPM	.05 GPM	4.3-85 PSI	1:500 to 1:50	.2-2%	3/4" NPT
		Mini Dos-1%	12 GPM	.03 GPM	6-140 PSI	1:500 to 1:100	.2-1%	3/4" NPT
	D14MZ2-14GPM	PVDF, PAA seals, bypass	14 GPM	.05 GPM	4.3-85 PSI	1:500 to 1:50	.2-2%	3/4" NPT
572CW		.4-4%, Aflas Seals, SS Springs	11 GPM	.09 GPM	2.9-120 PSI	1:250 to 1:25	.4-4%	3/4" NPT
573CW		.4-4% on/off, Aflas Seals, SS Springs	11 GPM	.09 GPM	2.9-120 PSI	1:250 to 1:25	.4-4%	3/4" NPT
572PVDF		.4-4%, PVDF, Viton Seals, HSTY Springs	11 GPM	.09 GPM	2.9-120 PSI	1:250 to 1:25	.4-4%	3/4" NPT
573PVDF		.4-4% on/off, PVDF, Viton Seals, HSTY Springs	11 GPM	.09 GPM	2.9-120 PSI	1:250 to 1:25	.4-4%	3/4" NPT
1405A		.5-5%, Aflas seals, HSTY Springs	14 GPM	.09 GPM	2.9-120 PSI	1:250 to 1:25	.4-4%	3/4" NPT
1405M		.5-5%, on/off, Aflas seals, HSTY Springs	14 GPM	.09 GPM	2.9-120 PSI	1:250 to 1:25	.4-4%	3/4" NPT
	D25RE5	PVDF, Side Inject, Bypass	11 GPM	.05 GPM	4.3-85 PSI	1:100 to 1:20	1-5%	3/4" NPT
		Mini Dos-2.5%	12 GPM	.03 GPM	6-140 PSI	1:200 to 1:40	.5-2.5%	3/4" NPT
		Mini Dos-5%	12 GPM	.03 GPM	6-140 PSI	1:100 to 1:20	1-5%	3/4" NPT
	D14MZ5-14GPM	PVDF, Bypass	14 GPM	.05 GPM	4.3-85 PSI	1:200 to 1:20	.5-5%	3/4" NPT
1410A		3-10%, Aflas Seals, SS Springs	14 GPM	.09 GPM	2.9-120 PSI	1:100 to 1:10	1-10%	3/4" NPT
1410M		3-10% on/off, Aflas Seals, SS Springs	14 GPM	.09 GPM	2.9-120 PSI	1:100 to 1:10	1-10%	3/4" NPT
		Mini Dos -10%	10 GPM	.03 GPM	6-65 PSI	1:50 to 1:10	2-10%	3/4" NPT
		Mini Dos -20%	7 GPM	.03 GPM	6-65 PSI	1:25 to 1:5	4-20%	3/4" NPT
	D14MZ10-14GPM	PVDF, Bypass	14 GPM	.05 GPM	7-85 PSI	1:100 to 1:10	1-10%	3/4" NPT



Mixrite Comparison Chart

Model		Options	Max Flow	Min Flow	Pressure	Induction Range		Connection
MixRite	Dosatron					Dosamatic	Ratio	
TF.5.001CL.PAAON/OFF		EPDM Seals for PAA	22 GPM	.8 GPM	2.9-120 PSI	1:1000 to 1:100	.1-1%	1" NPT
	D45RE15-20GPM		20 GPM	.4 GPM	7-70 PSI	1:500 to 1:66	.2-1.5%	1" NPT
	D45RE3000-20GPM		20 GPM	.4 GPM	7-70 PSI	1:3000 to 1:1000	.03-.1%	1" NPT
	SuperDos 20-0.3%		20 GPM	.04 GPM	5-100 PSI	1:4000 to 1:333	.025-.3%	1" NPT/BSP
TF.5.002ON/OFF		Buna Seals	22 GPM	.8 GPM	2.9-120 PSI	1:500 to 1:50	.2-2%	1" NPT
TF.5.002.V.ON/OFF		Viton Seals	22 GPM	.8 GPM	2.9-120 PSI	1:500 to 1:50	.2-2%	1" NPT
	D45RE3-20GPM		20 GPM	.4 GPM	7-70 PSI	1:200 to 1:33	.5-3%	1" NPT
	SuperDos 20-2.5%		20 GPM	.04 GPM	5-100 PSI	1:500 to 1:40	.2-2.5%	1" NPT/BSP
TF.5.005ON/OFF		Buna Seals	22 GPM	.8 GPM	2.9-120 PSI	1:200 to 1:20	.5-5%	1" NPT
	D45RE8-20GPM		20 GPM	.4 GPM	7-70 PSI	1:33-1:12	3-8%	1" NPT
	SuperDos 20-5%		20 GPM	.04 GPM	5-100 PSI	1:250 to 1:20	.4-5%	1" NPT/BSP
	SuperDos20-10%		20 GPM	.04 GPM	5-65 PSI	1:50 to 1:10	2-10%	1" NPT/BSP
TF.10.001CL.PAAON/OFF		EPDM Seals for PAA	45 GPM	2 GPM	14.7-120 PSI	1:1000 to 1:100	.1-1%	1 1/2" NPT
	SuperDos 45-0.3%		45 GPM	.5 GPM	5-100 PSI	1:4000 to 1:333	.025-.3%	1 1/4" NPT
TF.10.002		Buna Seals, Air Release Model	45 GPM	2 GPM	14.7-120 PSI	1:500 to 1:50	.2-2%	1 1/2" NPT
TF.10.002ON/OFF		Buna Seals, On/OFF Model	45 GPM	2 GPM	14.7-120 PSI	1:500 to 1:50	.2-2%	1 1/2" NPT
	D8R-40GPM		40 GPM	2.2 GPM	2-110 PSI	1:500 to 1:50	.2-2%	1 1/2" NPT
	SuperDos 45-2.5%		45 GPM	.5 GPM	5-100 PSI	1:500 to 1:40	.2-2.5%	1 1/4" NPT
TF.10.005ON/OFF		Buna Seals	45 GPM	2 GPM	14.7-120 PSI	1:100 to 1:20	1-5%	1 1/2" NPT
	D8R150-40GPM		40 GPM	2.2 GPM	2-110 PSI	1:100 to 1:20	1-5%	1 1/2" NPT
	SuperDos 45-5%		45 GPM	.5 GPM	5-80 PSI	1:250 to 1:20	.4-5%	1 1/4" NPT
TF.25.001CL.PAAON/OFF		EPDM Seals for PAA	110 GPM	9 GPM	14.7-120 PSI	1:1000 to 1:100	.1-1%	2" NPT
	TurboDos 100-0.25%		100 GPM	20 GPM	20-120 PSI	1:4000 to 1:400	.025-.25%	2" Flange
	TurboDos 100-0.5%		100 GPM	20 GPM	20-120 PSI	1:1000 to 1:200	.1-.5%	2" Flange
	TurboDos 100-0.1%		100 GPM	20 GPM	20-120 PSI	1:200 to 1:100	.5-1%	2" Flange
TF.25.002ON/OFF		Buna Seals	110 GPM	9 GPM	14.7-120 PSI	1:333 to 1:40	.3-2.5%	2" NPT
	D20S-100GPM		100 GPM	5 GPM	2-120 PSI	1:500 to 1:50	.2-2%	2" NPT
TF.25.005ON/OFF		Buna Seals	110 GPM	9 GPM	14.7-120 PSI	1:100 to 1:20	1-5%	2" NPT

